



NX-TRA

Model: 5-S2

KEY FEATURES

Max FPS @ Max Res	730 fps @ 2560 x 1920
Plus Mode	1455 fps @ 2560 x 1920
Max Frame Rate	60,000 fps @ 2336 x 16
Minimum Exposure Time	1 μ s
Sensitivity ASA	3000 ISO Mono 1000 ISO Color
Power Requirements	48VDC (with lights)
Operating Temperature	-40+50 °C / -40+122 °F
Memory Options	Internal RAM 1.25 GB / 3GB / 4GB / 5GB
Quantum Efficiency	50%

SENSOR

Sensor Type	CMOS - Proprietary
Sensor Size	16.4 x 12.1 mm
Sensor Format	1 inch
Image Size	5.0 megapixel
Pixel Size (micron)	7 x 7 μ m
Pixel Depth	10 bit mono 30 bit color

INPUTS

Trigger	TTL & Switch/Circular buffer with on-camera or software trigger
Sync	Phase-lock TTL
IRIG	N/A
GPS Time Code	N/A
YiFi	N/A

OUTPUTS

Sync	Frame sync / Strobe
HDMI	N/A
Comp Video	N/A



FEATURES

Approx. Size	69 x 64 x 64 mm or 2.7 x 2.5 x 2.5 in
Approx. Weight	0.2 kg or 0.5 lbs
Shock/Vibration rating	Shock: 200G / Vibration: 40G - All axes
Battery Powered Operation Time	N/A
Mount	C-Mount standard , F&PL Adaptor optional

SOFTWARE

Motion Studio	Windows 32/64
Motion Inspector	Windows 32/64, Mac OS, iOS
Plug-ins/SDK	SDK, LabVIEW™ or MatLab
File Formats	Proprietary RAW (MRF,MCF)
On-the-fly Conversion	TIF,BMP,JPG,PNG,AVI,MPG,TP2,MOV

COMMUNICATION

Camera Link	N/A
Ethernet	100/1000BaseT
USB 2.0	N/A
WiFi	N/A

Specifications are subject to change without notification.

Data accurate as of 07 August 2013

Please reference our website for updates: <http://www.idtvision.com>