

CMOS Cameras

MV2-D1280-640 SERIES

Build for demanding applications in industrial image processing

Features

- 1280 x 1024 pixel resolution
- Global shutter
- Dynamic range up to 60 dB
- Up to 490 fps @ full resolution
- Faster frame rates with Multiple Regions of Interest (MROI)
- CameraLink® interface
- 8 bit greyscale
- Superior Signal-to-Noise Ratio (SNR)
- 10 to 8 bit Look-up Table (LUT)
- y decimation for faster frame rates
- On shading correction
- Pixel Professor™ ready
- CE, RoHS & WEEE compliant



Application Examples

Machine vision

- Standard vision applications
- PCB inspection
- Laser triangulation

Motion analysis

- High-speed object tracking
- Slow-motion sequences
- Biomedical applications

Accessories

- Suitable power supply 12 Volt
- Power & signal connector 7 pin, (included in the shipment)
- CameraLink® cables
- A selection of suitable lenses is available on our website www.photonfocus.com. Lenses are not included.

Frame Grabber

A compatible frame grabber is available on request. Please contact us for more information.

MV2-D1280-640

Image Sensor

Technology	CMOS active pixel (APS)
Scanning system	Progressive scan
Optical format / diagonal	1.3" / 19.67 mm
Resolution	1280 x 1024 pixels
Pixel size	12.0 µm x 12.0 µm
Active optical area	15.36.9 mm x 12.29 mm
Random noise	To Be Defined (TBD)
Fixed pattern noise (FPN)	To Be Defined (TBD)
Dark current	To Be Defined (TBD)
Full well capacity	63 ke-
Spectral range	400 nm ... 900 nm
Responsivity	120 x 10 ³ DN / (J/m ²) @ 610 nm / 8 bit / gain = 1 (400 DN / (lux s) @ 610 nm / 8 bit / gain = 1)
Optical fill factor	40 %
Dynamic range	60 dB
Colour format	Monochrome
Characteristic curve	Linear
Shutter mode	Global shutter
Read out mode	Sequential or simultaneous read out

Camera

Exposure time	10 µs ... 34.5 s / 2 ns steps
Frame rate	Up to 490 fps
Pixel clock	82.5 MHz (8-tap mode), 66 MHz (10-tap mode)
Camera taps	8 or 10
Greyscale resolution	10 bit (internal) / 8 bit (CameraLink® output)
Analogue gain	1
Configuration interface	CL SERIAL (9600 baud or 57.6k baud user selectable)
Trigger modes	<ul style="list-style-type: none"> • Free running (non triggered) • Interface trigger • I/O Trigger
Features	<ul style="list-style-type: none"> • Multiple Regions of Interest (MROI) • Look-up Table (LUT) • On shading correction
Interface	CameraLink® Full, 8 bits, 8 or 10 taps
Operating temperature	0 °C ... +60 °C
Power supply	12 V DC (-10%) to +24 V DC (+10%); + 12V recommended
Power consumption	3 W (12 V supply voltage), 3.5 W (24 V supply voltage)
Lens mount	M42x1 or C-Mount
Dimensions	78 x 78 x 46.2 mm ³
Mass	374 g
Conformity	CE / RoHS / WEEE
Special	Pixel Professor™ optional

Software

Camera control	PFRemote™ graphical user interface (GUI) and PFLib (SDK)
----------------	--